

OSPW Compatibility

| Brand | Model | Stock | | | OSPW | | OSPW Spring Tension Settings |
|------------|-------------------------|-------|----------------|-------------|----------------|-------------|------------------------------|
| | | Gears | Cassette range | Pulley size | Cassette range | Pulley size | |
| Shimano | Dura Ace 9250 | 12 | 34 | 11/11 | 34 | 13/19 | 4 |
| | Ultegra 8150 | 12 | 34 | 11/11 | 34 | 13/19 | 4 |
| | Dura Ace 9100/9150 | 11 | 30 | 11/11 | 32 | 13/19 | 4 |
| | Ultegra 8000/8050 SS | 11 | 32 | 11/11 | | | |
| | Dura Ace 9000/9070 | 11 | 28 | 11/11 | 28 | 17/17 | 3 |
| | Ultegra 6800/6870 SS/GS | 11 | 28 | 11/11 | | | |
| | Ultegra RX800/RX805 | 11 | 32 | 11/11 | 36 | 13/19 | 4 |
| | GRX810/GRX815 | 11 | 34 | 11/11 | | | |
| | XTR 9100 | 12 | 51 | 13/13 | 51 | 14/18 | 2 |
| | XT 8100 | 12 | 51 | 13/13 | | | |
| | SLX 7100 | 12 | 51 | 13/13 | | | |
| Campagnolo | Super Record 12spd EPS | 12 | 32 | 12/12 | 34 | 13/19 | 3 |
| | Super Record EPS | 11 | 29 | 11/11 | 30 | 13/19 | 3 |
| | Record EPS | 11 | 29 | 11/11 | | | |
| | Chorus EPS | 11 | 29 | 11/11 | | | |
| | Super Record | 11 | 29 | 11/11 | 32 | | |
| | Record | 11 | 32 | 11/11 | | | |
| | Chorus | 11 | 32 | 11/11 | | | |
| | Potenza | 11 | 32 | 11/11 | | | |

Notes:

- Adjustment of spring tension can allow for customization of user experience. Higher spring tension can focus on chain retention and crisp shift response. Lower spring tension will reduce chain drag and improve overall efficiency.
- The CeramicSpeed OSPW cage design has been tested for aerodynamic impacts in multiple wind tunnels. No measurable adverse aerodynamic impacts were measured through a variety of yaw angles.
- Shimano Ultegra R8000 GS, R8050 GS, and 105 derailleurs are not compatible with any CeramicSpeed OSPW system.
- Campagnolo 12spd Mechanical derailleurs are not compatible with any CeramicSpeed OSPW System.

| Brand | Model | Gears | Stock | | OSPW | | OSPW Spring Tension Settings |
|-----------|-----------------------------|-------|----------------|-------------|----------------|-------------|------------------------------|
| | | | Cassette range | Pulley size | Cassette range | Pulley size | |
| SRAM | Red eTap AXS | 12 | 33 | 12/12 | 36 | 15/19 | 2 |
| | Red eTap AXS (wide range) | 12 | 36 | 12/12 | | | |
| | Force eTap AXS | 12 | 33 | 12/12 | | | |
| | Force eTap AXS (wide range) | 12 | 36 | 12/12 | | | |
| | Rival eTap AXS | 12 | 36 | 12/12 | *Coming 2022 | | |
| | Red XPLR eTap AXS | 12 | 44 | 12/12 | *Coming 2022 | | |
| | Force XPLR eTap AXS | 12 | 44 | 12/12 | *Coming 2022 | | |
| | Rival XPLR eTap AXS | 12 | 44 | 12/12 | *Coming 2022 | | |
| | Red eTap | 11 | 28 | 11/11 | 32 | 17/17 | 3 |
| | Red eTap WiFli | 11 | 32 | 11/11 | | | |
| | Red eTap w/Clutch | 11 | 32 | 12/12 | 32 | 15/19 | 2 |
| | Red 22 | 11 | 28 | 11/11 | 32 | 17/17 | 3 |
| | Red 22 WiFli | 11 | 32 | 11/11 | | | |
| | Force 22 | 11 | 28 | 11/11 | | | |
| | Force 22 WiFli | 11 | 32 | 11/11 | | | |
| | Force 1 (w/Type 3 clutch) | 11 | 42 | 12/12 | 42 | 14/18 | 2 |
| | Rival 1 (w/Type 3 clutch) | 11 | 42 | 12/12 | | | |
| | Eagle Mech | 12 | 52 | 12/14 | 52 | 14/18 | 3 |
| Eagle AXS | 12 | 52 | 12/14 | 52 | 14/18 | 3 | |

Notes:

- Adjustment of spring tension can allow for customization of user experience. Higher spring tension can focus on chain retention and crisp shift response. Lower spring tension will reduce chain drag and improve overall efficiency.
- The CeramicSpeed OSPW cage design has been tested for aerodynamic impacts in multiple wind tunnels. No measurable adverse aerodynamic impacts were measured through a variety of yaw angles.
- SRAM Rival, & SRAM Apex derailleurs are not compatible with any CeramicSpeed OSPW system.